PX-0122-INO


V0

Stair Empotrable de pared



Descripción
Empotrable de pared IP54 Stair LED 1W 3000K ON-OFF Pulido Gris 5lm

	Acabado	Material
Estructura	Pulido Gris	Acero inoxidable AISI 304 Policarbonato
Difusor	Blanco	Acrílico



IP54 IK10 ULTRA HORIZONTAL 40

UGR	
S=0.250	
Techo/Cavidad	0.7
Paredes	0.5
Plano De Trabajo	0.2
Dimensiones De La Habitación	X=4H, Y=8H
UGR Transversal	17.3
UGR Longitudinal	16.7

CARACTERÍSTICAS TÉCNICAS

Fuente de luz
Fuente de luz: LED SUNPU
Potencia (W): 1W
Consumo total (W): 1.3
Temperatura de color: Blanco cálido - 3000K
CRI: 80
Riesgo fotobiológico: RG0
Lumens reales: 5
Nº Leds: 12
Lm/W reales: 4
Vida útil: 36.000h L70B30
Bin / Grup: Wi9
MacAdam steps: 3
UGR: 13.3
Bombilla recomendada: LED

EQUIPO
Marca: DRIVER AC
Equipo incluido: Si, electrónico
Voltaje / Frecuencia: 100-240V/50-60Hz
Protocolo de regulación: ON-OFF

Luminaria
Drenaje: Sí
Metros cable incluido: Sí
Protección UVA: Sí
Garantía: 5 Años

Logística
Eficiencia energética: LED A++
EAN: 8435381439828
Peso neto (Kg): 0.15
Peso en Kg (embalado): 0.19
Box: 115 x 50 x 70
Masterbox: 40

El acabado de la fotografía puede no coincidir con el de la referencia. Para identificar el real ver descripción del acabado.

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Rectangular Luminaire	Length	45 mm	Width	110 mm	Height	2 mm
Rectangular Luminous Area	Length	23 mm	Width	59 mm	Height	0 mm

Horizontal Luminous Area	0.001357 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000328 m2

Coordinate system	CG	Symmetry Type	Asymmetrical
Date	03-06-2016	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	5.28 lm


Operator	Asselum T3	Source Voltage [V]	
Temperature	25.00 °C	Source current [A]	
Humidity	60.00 %	Photocell	
Notes			

Luminaire Lamps

Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
	PX-0122-INO	PX-0122-INO	5.28	1.00	1


C.I.E.	47 80 97 100 100	D DIN 5040	A30
F UTE	1.00 E	B NBN	BZ 4

45mm x 110mm



C Halfplanes

180.0 — 0.0
270.0 — 90.0



ULOR	0.00 %
DLOR	100.00 %
RN	0.00 %

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Luminous Intensity Table cd/klm **Table 1/1**


	C 0.00	C 15.00	C 30.00	C 45.00	C 60.00	C 75.00	C 90.00	C 105.00	C 120.00	C 135.00	C 150.00	C 165.00
G 0.0	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88
G 5.0	348.89	349.18	349.23	348.92	348.87	349.13	349.41	349.07	349.28	349.33	349.38	349.53
G 10.0	344.30	344.39	344.38	344.54	344.49	344.28	344.51	344.58	344.70	344.42	344.88	345.21
G 15.0	337.01	337.27	337.51	336.91	336.45	336.25	336.78	336.26	337.16	337.13	337.23	337.90
G 20.0	327.10	327.32	327.24	326.39	326.19	326.20	325.84	326.35	327.09	326.81	327.19	327.45
G 25.0	313.73	314.07	314.22	313.34	312.53	313.11	312.69	313.74	313.58	313.50	314.53	314.84
G 30.0	299.17	298.75	299.15	297.62	297.16	296.73	297.01	297.16	298.20	299.07	299.05	299.73
G 35.0	281.34	280.82	280.51	279.38	278.81	278.85	278.34	279.70	279.26	280.25	281.07	281.53
G 40.0	260.10	261.39	259.90	258.85	257.52	257.62	257.05	258.21	258.74	260.19	260.90	262.04
G 45.0	238.35	238.39	237.25	236.88	234.64	235.36	234.05	235.29	235.15	236.97	237.64	238.82
G 50.0	213.86	214.83	213.25	211.56	210.53	209.55	208.59	210.38	210.82	213.03	213.61	215.03
G 55.0	187.44	187.45	186.69	185.47	182.55	183.02	181.15	183.68	182.55	185.37	186.10	188.50
G 60.0	159.04	159.98	158.00	157.08	154.21	152.15	152.55	152.27	154.33	157.29	158.27	160.26
G 65.0	128.82	129.64	127.59	126.37	122.15	122.12	119.99	122.66	123.14	125.64	127.04	129.73
G 70.0	98.26	98.49	96.11	94.53	90.67	89.53	88.09	89.81	90.33	94.69	96.21	98.45
G 75.0	65.30	65.94	63.78	61.17	57.64	55.82	54.08	56.00	58.20	61.00	63.72	65.75
G 80.0	35.43	35.96	32.37	30.32	28.33	26.43	24.74	25.63	26.25	30.43	32.12	36.40
G 85.0	10.09	10.01	8.17	6.79	4.58	3.81	3.04	3.86	3.86	6.13	8.00	10.24
G 90.0	0.66	0.70	0.69	0.70	0.72	0.75	0.77	0.74	0.71	0.70	0.70	0.73

	C 180.00	C 195.00	C 210.00	C 225.00	C 240.00	C 255.00	C 270.00	C 285.00	C 300.00	C 315.00	C 330.00	C 345.00
G 0.0	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88	350.88
G 5.0	349.50	349.42	349.54	349.39	349.13	349.18	349.36	349.07	349.33	349.13	349.43	349.53
G 10.0	345.11	345.11	345.20	344.97	345.01	344.39	344.61	344.73	345.00	345.04	345.09	345.04
G 15.0	337.95	338.20	338.08	337.84	337.38	337.33	337.19	337.45	337.57	337.75	337.59	337.83
G 20.0	328.36	328.25	327.91	328.04	327.27	327.13	326.51	327.48	326.94	327.30	327.91	328.02
G 25.0	315.37	316.19	315.67	314.84	314.02	313.58	313.67	314.00	314.35	314.74	314.95	315.87
G 30.0	300.32	300.51	299.72	299.94	298.61	298.74	298.30	298.76	298.09	299.64	299.57	300.20
G 35.0	282.02	283.45	282.58	281.32	280.10	279.73	279.58	280.39	280.50	282.11	281.66	283.29
G 40.0	262.27	262.19	262.39	260.58	260.20	258.82	259.41	259.43	259.34	260.73	261.49	262.60
G 45.0	239.29	240.29	239.83	238.39	237.15	235.81	236.00	236.47	237.36	238.80	239.82	240.25
G 50.0	215.62	215.83	216.13	213.58	212.46	211.47	211.81	211.38	212.54	214.60	214.68	215.81
G 55.0	189.70	189.22	188.45	186.80	186.21	184.23	183.60	184.02	185.45	186.94	188.87	188.44
G 60.0	160.67	160.51	160.83	157.99	156.47	154.94	153.46	154.68	157.28	158.10	159.43	160.67
G 65.0	130.35	130.13	129.27	127.21	125.20	123.54	122.61	124.15	125.30	127.16	129.87	130.38
G 70.0	98.02	99.23	98.79	95.84	93.32	90.56	89.71	90.13	93.79	95.68	97.42	98.54
G 75.0	66.94	65.92	64.75	61.69	58.74	56.49	56.07	57.04	58.94	61.71	65.31	67.28
G 80.0	35.09	35.67	33.89	30.30	27.86	26.08	25.00	25.72	27.97	30.32	32.99	35.16
G 85.0	10.69	10.01	8.48	6.12	4.79	3.30	3.47	3.57	4.90	6.14	8.49	9.59
G 90.0	0.70	0.83	0.67	0.67	0.70	0.73	0.76	0.76	0.74	0.73	0.72	0.72

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical


45mm x 110mm



C Halfplanes

180.0 0.0

270.0 90.0



Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W


Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Width at 50.00 % of Max Intensity


H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.55	3.10	4.65	6.20	7.75	OC	1.48	2.97	4.45	5.94	7.42
OB	1.57	3.14	4.71	6.28	7.85	OD	1.50	3.01	4.51	6.01	7.52

Luminous Intensities [cd/klm]


	0	5	15	25	35	45	55	65	75	85
OA	1.85	1.84	1.78	1.66	1.49	1.26	0.99	0.68	0.34	0.05
OB	1.85	1.85	1.78	1.67	1.49	1.26	1.00	0.69	0.35	0.06
OC	1.85	1.84	1.78	1.65	1.47	1.24	0.96	0.63	0.29	0.02
OD	1.85	1.84	1.78	1.66	1.48	1.25	0.97	0.65	0.30	0.02



H[m]	D[m]	Max lux	Med lux
1.00	3.12	2	0
2.00	6.24	0	0
3.00	9.36	0	0
4.00	12.48	0	0
5.00	15.59	0	0



H[m]	D[m]	Max lux	Med lux
1.00	2.99	2	0
2.00	5.98	0	0
3.00	8.96	0	0
4.00	11.95	0	0
5.00	14.94	0	0



Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical


UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	13.4	14.8	13.7	15.0	15.1	13.3	14.6	13.6	14.8	15.1
x=2H y=3H	15.1	16.3	15.4	16.5	16.5	14.8	16.0	15.1	16.2	16.5
x=2H y=4H	15.7	16.8	16.0	17.1	17.0	15.3	16.4	15.6	16.7	17.0
x=2H y=6H	16.1	17.1	16.4	17.4	17.2	15.5	16.5	15.9	16.8	17.2
x=2H y=8H	16.2	17.2	16.5	17.5	17.2	15.5	16.5	15.9	16.8	17.2
x=2H y=12H	16.2	17.1	16.6	17.5	17.1	15.5	16.5	15.9	16.8	17.1
x=4H y=2H	14.2	15.3	14.5	15.6	15.8	14.1	15.2	14.4	15.5	15.8
x=4H y=3H	16.0	16.9	16.4	17.3	17.3	15.7	16.7	16.1	17.0	17.3
x=4H y=4H	16.7	17.6	17.1	17.9	17.9	16.3	17.2	16.7	17.5	17.9
x=4H y=6H	17.2	17.9	17.6	18.3	18.2	16.6	17.4	17.1	17.8	18.2
x=4H y=8H	17.3	18.0	17.8	18.4	18.2	16.7	17.4	17.1	17.8	18.2
x=4H y=12H	17.4	18.0	17.8	18.4	18.1	16.7	17.3	17.1	17.7	18.1
x=8H y=4H	17.0	17.6	17.4	18.0	18.1	16.6	17.3	17.1	17.7	18.1
x=8H y=6H	17.6	18.1	18.0	18.5	18.5	17.0	17.6	17.5	18.0	18.5
x=8H y=8H	17.7	18.2	18.2	18.7	18.5	17.1	17.6	17.6	18.0	18.5
x=8H y=12H	17.8	18.2	18.3	18.7	18.5	17.1	17.5	17.6	18.0	18.5
x=12H y=4H	17.0	17.6	17.4	18.0	18.1	16.6	17.3	17.1	17.7	18.1
x=12H y=6H	17.6	18.1	18.1	18.5	18.5	17.1	17.5	17.5	18.0	18.5
x=12H y=8H	17.8	18.2	18.3	18.6	18.5	17.1	17.6	17.6	18.0	18.5

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W


Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

45mm x 110mm



C Halfplanes


180.0 0.0
270.0 90.0



Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Luminance



Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Luminance cd/m2 **Table 1/3**

	C 0.00	C 10.00	C 20.00	C 30.00	C 40.00	C 50.00	C 60.00	C 70.00	C 80.00	C 90.00	C 100.00	C 110.00	C 120.00
G 0.0	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26
G 5.0	1362.69	1363.50	1364.06	1364.02	1363.22	1362.59	1362.62	1363.18	1364.19	1364.73	1363.79	1363.48	1364.23
G 10.0	1360.30	1360.61	1360.64	1360.62	1361.04	1361.34	1361.06	1360.38	1360.46	1361.16	1361.32	1361.67	1361.91
G 15.0	1357.56	1358.16	1359.13	1359.55	1358.08	1356.40	1355.27	1354.31	1355.28	1356.60	1354.95	1355.35	1358.13
G 20.0	1354.41	1355.05	1355.53	1354.97	1352.60	1351.19	1350.63	1350.66	1350.15	1349.21	1350.17	1352.61	1354.38
G 25.0	1346.91	1347.85	1348.88	1349.02	1346.89	1343.51	1341.72	1343.63	1343.71	1342.44	1345.41	1346.71	1346.24
G 30.0	1344.14	1342.26	1343.15	1344.04	1339.57	1335.91	1335.12	1333.62	1333.37	1334.44	1334.66	1336.26	1339.76
G 35.0	1336.35	1334.49	1333.56	1332.41	1328.93	1325.56	1324.33	1324.83	1323.72	1322.12	1326.74	1328.40	1326.47
G 40.0	1321.12	1326.95	1326.04	1320.10	1316.52	1312.24	1308.03	1308.42	1307.44	1305.62	1309.39	1312.59	1314.19
G 45.0	1311.54	1312.56	1309.68	1305.47	1305.11	1299.16	1291.13	1294.01	1293.11	1287.87	1292.32	1294.81	1293.96
G 50.0	1294.51	1299.95	1298.53	1290.84	1283.54	1278.17	1274.38	1270.88	1265.37	1262.67	1269.93	1274.65	1276.16
G 55.0	1271.54	1272.17	1270.17	1266.43	1262.66	1250.79	1238.38	1241.20	1237.00	1228.84	1241.03	1244.56	1238.35
G 60.0	1237.59	1245.05	1240.83	1229.53	1225.25	1216.48	1200.05	1186.91	1184.26	1187.16	1185.00	1187.88	1200.95
G 65.0	1186.01	1194.14	1188.24	1174.71	1169.82	1150.47	1124.62	1124.45	1117.57	1104.69	1120.32	1132.40	1133.71
G 70.0	1117.80	1122.97	1112.61	1093.36	1083.46	1061.35	1031.49	1021.92	1011.80	1002.15	1015.25	1022.63	1027.59
G 75.0	981.71	992.23	983.80	958.84	934.30	901.46	866.45	847.66	827.91	813.07	828.90	853.34	874.94
G 80.0	793.79	811.87	784.11	725.26	691.39	665.37	634.82	607.23	575.60	554.44	567.23	574.89	588.13
G 85.0	450.46	448.03	423.43	364.55	325.95	270.25	204.61	179.26	155.44	135.93	161.50	170.97	172.17
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Luminance cd/m2 **Table 2/3**

	C 130.00	C 140.00	C 150.00	C 160.00	C 170.00	C 180.00	C 190.00	C 200.00	C 210.00	C 220.00	C 230.00	C 240.00	C 250.00
G 0.0	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26
G 5.0	1364.35	1364.48	1364.60	1365.04	1365.25	1365.06	1364.76	1364.89	1365.23	1364.97	1364.26	1363.63	1363.59
G 10.0	1361.02	1361.12	1362.62	1363.72	1363.80	1363.53	1363.41	1363.64	1363.89	1363.18	1363.01	1363.11	1361.34
G 15.0	1358.05	1357.80	1358.41	1360.36	1361.18	1361.31	1362.03	1362.34	1361.84	1361.31	1360.22	1359.02	1358.86
G 20.0	1353.58	1353.49	1354.77	1355.27	1357.07	1359.63	1359.76	1358.47	1357.76	1358.41	1357.39	1355.12	1354.87
G 25.0	1345.41	1347.22	1350.35	1351.43	1352.08	1353.94	1356.69	1357.27	1355.22	1352.85	1350.43	1348.15	1346.61
G 30.0	1342.90	1343.76	1343.59	1345.44	1347.67	1349.28	1350.47	1348.92	1346.60	1347.69	1345.86	1341.60	1341.99
G 35.0	1329.09	1332.82	1335.05	1336.72	1337.59	1339.58	1344.75	1346.10	1342.23	1338.25	1334.11	1330.45	1329.10
G 40.0	1319.14	1323.04	1325.17	1329.13	1331.99	1332.16	1331.86	1332.06	1332.77	1326.43	1322.49	1321.60	1316.49
G 45.0	1300.44	1305.81	1307.66	1312.08	1315.15	1316.70	1320.68	1322.48	1319.67	1314.40	1309.49	1304.95	1299.40
G 50.0	1285.25	1291.50	1293.01	1298.56	1303.64	1305.21	1305.56	1308.11	1308.27	1298.23	1289.58	1286.06	1281.41
G 55.0	1250.54	1260.41	1262.41	1272.71	1283.17	1286.83	1285.09	1282.34	1278.38	1270.41	1265.79	1263.21	1254.26
G 60.0	1217.79	1227.31	1231.65	1242.13	1249.93	1250.35	1249.47	1249.87	1251.55	1237.45	1224.02	1217.62	1210.33
G 65.0	1148.73	1161.61	1169.65	1186.66	1198.70	1200.13	1199.06	1196.46	1190.11	1178.10	1164.62	1152.69	1142.34
G 70.0	1060.92	1085.82	1094.55	1113.37	1120.16	1115.15	1123.59	1131.14	1123.85	1102.14	1080.33	1061.60	1039.26
G 75.0	902.19	931.52	957.87	979.09	997.27	1006.32	997.37	986.25	973.41	944.41	911.52	883.00	858.17
G 80.0	652.65	695.77	719.80	790.91	805.84	786.23	793.59	794.82	759.38	705.01	657.30	624.26	596.75
G 85.0	235.43	303.55	357.02	427.88	473.89	477.40	460.70	429.71	378.65	305.63	250.76	214.03	164.09
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency 100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG Asymmetrical

Luminance cd/m2 **Table 3/3**


	C 260.00	C 270.00	C 280.00	C 290.00	C 300.00	C 310.00	C 320.00	C 330.00	C 340.00	C 350.00
G 0.0	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26	1365.26
G 5.0	1364.20	1364.53	1363.66	1363.66	1364.42	1363.87	1363.81	1364.82	1365.39	1364.62
G 10.0	1360.64	1361.56	1361.88	1362.34	1363.09	1363.19	1363.25	1363.42	1363.54	1362.51
G 15.0	1358.61	1358.27	1358.93	1359.52	1359.79	1360.43	1360.28	1359.86	1360.72	1360.22
G 20.0	1353.44	1351.97	1354.83	1355.74	1353.74	1354.30	1356.20	1357.77	1358.52	1357.33
G 25.0	1346.16	1346.65	1347.56	1348.50	1349.55	1350.86	1351.23	1352.13	1355.60	1354.41
G 30.0	1341.59	1340.23	1342.01	1341.14	1339.29	1343.99	1346.14	1345.92	1348.05	1348.13
G 35.0	1328.12	1328.00	1330.82	1332.00	1332.36	1338.12	1339.51	1337.88	1343.59	1344.55
G 40.0	1315.61	1317.63	1317.69	1317.57	1317.28	1321.98	1325.68	1328.18	1333.16	1331.46
G 45.0	1297.11	1298.63	1300.29	1302.42	1306.10	1311.43	1316.13	1319.64	1322.36	1319.72
G 50.0	1280.42	1282.16	1280.20	1280.36	1286.57	1296.00	1299.18	1299.48	1304.96	1304.54
G 55.0	1247.00	1245.48	1246.56	1251.17	1258.04	1264.24	1273.05	1281.20	1280.54	1275.96
G 60.0	1200.80	1194.21	1198.13	1210.82	1223.92	1228.84	1232.82	1240.66	1249.03	1248.25
G 65.0	1132.69	1128.88	1137.51	1147.14	1153.57	1163.50	1179.47	1195.65	1201.54	1196.89
G 70.0	1024.91	1020.60	1019.80	1037.48	1066.95	1083.03	1094.69	1108.23	1118.55	1121.35
G 75.0	844.04	842.93	850.91	865.70	886.09	912.01	945.52	981.88	1007.85	1006.76
G 80.0	573.46	560.24	565.91	590.99	626.79	661.41	698.59	739.27	775.78	789.82
G 85.0	149.86	154.97	157.87	175.05	218.57	251.58	307.42	379.24	418.21	436.52
G 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

PERCENTAGE ISOCANDLES

Projection: Equal Area SLI (glare) 13.0 Tight Tilting Angle:0°



Spread: 23.9° Narrow


Throw: 12.2° Short

Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W

Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=2.50m



Luminaire
Code PX-0122-INO
Name Empotrable pared STAIR 1W
Measurem.
Code PX-0122-INO
Name Empotrable pared STAIR 1W


Luminaire Flux	5.28 lm	Luminaire Power	1.00 W	Efficacy	5.28 lm/W	Efficiency	100.00%
Lamps Flux	5.28 lm	Maximum value	350.88 cd/klm	Position	C=0.00 G=0.00	CG	Asymmetrical


Average Luminance [cd/m²]


	45°	50°	55°	60°	65°	70°	75°	80°	85°	
0.0°	1312	1295	1272	1238	1186	1118	982	794	450	---
90.0°	1288	1263	1229	1187	1105	1002	813	554	136	---


Flush mounted or longitudinal view

		Illumination(lx)										
A	A	2000	1000	750	500		<300					1.15
B	1		2000	1500	1000	750	500	<300				1.5
C					2000		1000	500	<300			1.85
D	2						2000	1000	500	<300		2.2
E	3							2000	1000	500	<300	2.55





110
45
43
PC
250mm



CRISTAL PINTADO BLANCO EN
LA PARTE INTERIOR
GLASS WHITE PAINTED INSIDE
ACERO INOXIDABLE AISI 304
STAINLESS STEEL AISI 304


104
52,5
40
CAJA DE EMPOTRAR
FLUSH FITTING BOX


A①




B①




A②



B②




A③




a


b




B③



A④



A⑤



A⑥

B④

